

2PSA | All-Purpose, Single Axle Utility

Shown with Optional 48" Bi-Fold Ramp Gate

GVWR: 2,990 lbs
BED LENGTHS: 8'-14'
BED WIDTH: 60", 77" or 83"



BALLED END PIPE TOP-RAIL
Permanently sealed, safe, and ergonomic

BOXED TAIL LIGHTS
Lights are waterproof, rubber-mounted, and the mounting box is raised to the top-rail for increased protection and visibility.

TOP RAIL CHOICES

~ 2-3/8" PIPE with **BALLED ENDS**: Permanently sealed and ergonomic,
~ 2" x 2" x 1/8" **ANGLE IRON**, or
~ 2" **SQ. TUBE**



GATE OPTION

Optional 48" Bi-Fold Gate offers reduced wind-drag and less obstruction when compared to traditional straight gates. Easy to use and safe. (Straight Gate also available)

JACK
2000 lb Top-Wind Jack, with Bolted-on Foot

DECK
2" Treated Lumber

GRAVEL GUARD
Protects fenders from rocks and debris


DEXTER AXLE
3500 lb E-Z Lube for quick and easy lubrication

TIRES
ST205/75D15

WIRING
Concealed and protected in the tube framing

FRAME & CROSS MEMBERS
Unique Rectangle Tube Frame and Square Tube Cross-Members provide flush-floor and improved under-carriage ground clearances

TIE DOWNS
4 - ATV Tie Downs
1 located in each corner of the trailer

STAKE POCKETS
4 Stake Pockets used as tie down points

TONGUE
3" x 1-1/2" Rectangle Tube

COUPLER
2" - 5000 lb Capacity "A-Frame"



Diamond C uses road-tested DuPont polyurethanes that provide the trailers with a long-lasting, rugged, and beautiful finish.

Specifications, standard features, options, components, and colors are subject to change without notice. Some features may be subject availability, delays, or discontinuance.

Standard Premium Dupont Paint Colors
Custom colors available upon request.

